





Multi binnendelen artikelnummers				
Capaciteit	2,5kW	3,5kW	5,3kW	7kW
 <b>Wand</b>	1869076	1869077	1869078	1869079
<i>flua</i>	¼ - ¾	¼ - ¾	¼ - ½	¼ - ¾
 <b>Cassette</b>		1869091	1869092	
<b>Paneel</b>		1869058	1869058	
		¼ - ¾	¼ - ½	
 <b>Kanaal</b>		1869101	1869102	
		¼ - ¾	¼ - ½	
 <b>Console</b>		1869106	1869107	
		¼ - ¾	¼ - ½	

\* Leidingdiameter binnendeel bepaalt leidingdiameter naar buitendeel

Multi buitendelen				
Totale koelcapaciteit Nominaal (Min-Max) kW	<b>5.28</b> (2.23-5.71)	<b>7.91</b> (2.10-8.50)	<b>10.55</b> (2.05-12.66)	<b>12.31</b> (2.05-14.16)
Totale koelcapaciteit Nominaal (Min-Max) Btu/h	18.000 (4.500-19.000)	27.000 (7.170-29.000)	36.000 (7.000-43.200)	42.000 (7.000-48.300)
Totale verwarmingscapaciteit Nominaal (Min-Max) kW	5.57 (2.34-5.86)	7.91 (1.96-8.79)	10.55 (2.34-12.98)	12.31 (2.34-14.77)
Totale verwarmingscapaciteit Nominaal (Min-Max) Btu/h	19.000 (6.400-19.600)	27.000 (6.700-30.000)	36.000 (8.000-44.300)	42.000 (8.000-50.400)
Aansluitingen Vloeistof+Gas *	2x 1/4-3/8	3x 1/4-3/8	3x 1/4-3/8 + 1x 1/4-1/2	4x 1/4-3/8 + 1x 1/4-1/2
Aantal binnendelen Min Max	Min 1 Max 2	Min 1 Max 3	Min 1 Max 4	Min 1 Max 5
Geluidsniveau dB(A)	64	67	63	62
Geluidsvermogen dB(A)	56	53	68	71
Voeding V/Aders mm²/Afzekerwaarde A	220V/3x2.5/1x16A	220V/3x2.5/1x20A	220V/3x4.0/1x25A	220V/3x4.0/1x25A
Communicatie kabel mm²	4x1,5	4x1,5	4x1,5	4x1,5
Bijvullen na 7,5 meter per binnendeel	12g/m	12g/m	12g/m 1/4 24g/m 3/8	12g/m 1/4 24g/m 3/8
Afmetingen Lengte Breedte Hoogte	800x333x554mm	845x363x702mm	946x410x810mm	946x410x810mm
Gewicht (Kg)	35.5	51.1	68.8	73.3
Compressor type	Rotary	Rotary	Rotary	Rotary
R32 vulgewicht (Kg)	1.25	1.72	2.10	2.40
Leidinglengte totaal max (meter)	40	60	80	80
Leidinglengte per binnen unit max (meter)	25	30	35	35
Maximale hoogte verschil binnen-buiten unit (meter)	15	15	15	15
Maximale hoogte verschil binnen-binnen units (meter)	10	10	10	10
Buitendeel type	U5MRS132(2)-18B	U5MRS132(3)-27B	U5MRS132(4)-36	U5MRS132(5)-42
Buitendeel artikelnummer	1869070	1869071	1869072	1869073



Combinatie binnendelen aantal					
	1	2	3	4	5
Btu/h kW	Btu/h kW	Btu/h kW	Btu/h kW	Btu/h kW	Btu/h kW
9K 2,5kW					
12K 3,5kW					
18K 5,3kW					
24K 7,0kW					
9K 2,5kW	9K 2,5kW				
9K 2,5kW	12K 3,5kW				
9K 2,5kW	18K 5,3kW				
9K 2,5kW	24K 7,0kW				
12K 3,5kW	12K 3,5kW				
12K 3,5kW	18K 5,3kW				
12K 3,5kW	24K 7,0kW				
18K 5,3kW	18K 5,3kW				
9K 2,5kW	9K 2,5kW	9K 2,5kW			
9K 2,5kW	9K 2,5kW	12K 3,5kW			
9K 2,5kW	9K 2,5kW	18K 5,3kW			
9K 2,5kW	9K 2,5kW	24K 7,0kW			
9K 2,5kW	9K 2,5kW	12K 3,5kW	12K 3,5kW		
9K 2,5kW	12K 3,5kW	18K 5,3kW			
9K 2,5kW	12K 3,5kW	24K 7,0kW			
9K 2,5kW	18K 5,3kW	18K 5,3kW			
12K 3,5kW	12K 3,5kW	12K 3,5kW			
12K 3,5kW	12K 3,5kW	18K 5,3kW			
12K 3,5kW	12K 3,5kW	24K 7,0kW			
12K 3,5kW	18K 5,3kW	18K 5,3kW			
9K 2,5kW	9K 2,5kW	9K 2,5kW	9K 2,5kW		
9K 2,5kW	9K 2,5kW	9K 2,5kW	12K 3,5kW		
9K 2,5kW	9K 2,5kW	9K 2,5kW	18K 5,3kW		
9K 2,5kW	9K 2,5kW	9K 2,5kW	24K 7,0kW		
9K 2,5kW	9K 2,5kW	12K 3,5kW	12K 3,5kW		
9K 2,5kW	9K 2,5kW	12K 3,5kW	18K 5,3kW		
9K 2,5kW	9K 2,5kW	12K 3,5kW	24K 7,0kW		
9K 2,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW		
9K 2,5kW	12K 3,5kW	12K 3,5kW	18K 5,3kW		
12K 3,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW		
12K 3,5kW	12K 3,5kW	12K 3,5kW	18K 5,3kW		
9K 2,5kW	9K 2,5kW	9K 2,5kW	9K 2,5kW	9K 2,5kW	
9K 2,5kW	9K 2,5kW	9K 2,5kW	9K 2,5kW	12K 3,5kW	
9K 2,5kW	9K 2,5kW	9K 2,5kW	9K 2,5kW	18K 5,3kW	
9K 2,5kW	9K 2,5kW	9K 2,5kW	12K 3,5kW	12K 3,5kW	
9K 2,5kW	9K 2,5kW	9K 2,5kW	12K 3,5kW	18K 5,3kW	
9K 2,5kW	9K 2,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW	
9K 2,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW	
12K 3,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW	12K 3,5kW	